

TANILED



CONTACT US



Komplek Perkantoran Multiguna Kemayoran
Blok 5 OK Jl. Rajawali Selatan Raya Kavling
C-5 No. 2 Kel. Pademangan Timur,
Kec. Pademangan, Jakarta Utara, DKI Jakarta - 14410
Telp : 021 - 6412557

GOB
Modular Series
Glue-On-Board Modular Indoor

1.53

PROJECT IMPLEMENTATION



AUDITORIUM



MULTIFUNCTION ROOM



RETAIL



WORSHIP

TANILED GOB uses Glue on Board (GOB) technology to provide maximum protection for the LED surface. It offers higher resistance to impact, dust, and high humidity, ensuring stable and reliable performance for long-term use in various environmental conditions.

PRODUCT SPECIFICATION

Parameter	Value
Pixel Pitch (mm)	1,53
LED Type	GOB
Modul Size (W*H, mm)	320 x 160
Modul Resolution (W*H, pixel)	208x104
Module Weight (Kg)	≥0,41
Pixel Density (Pixel/m ²)	427.186
Brightness (cd/m ²)	≥600
Color temperature(K)	6500K
Power Consumption (Max. AVG.) (W/m ²)	≤450w/m ² 150-220w/m ²
Refresh Rate (Hz)	7680
Viewing Angel (H/V)°	≥160 /≥160
Input Signal	HDMI, DVI/VGA.RGBH Composite, S-Video, YPbPr(HDTV) etc.
IP Rate	Front IP65, rear IP30
Recommend View Distance (m)	≥2m~33m
Operating Humidity Range (RH)	10%~95%
Maintenance	Front
Lifespan(Hours)	100.000

Catatan:

Disarankan menyiapkan spare daya sekitar 30% agar LED Display bekerja lebih stabil dan menghadirkan performa terbaik setiap saat