

TANILED



CONTACT US



Komplek Perkantoran Multiguna Kemayoran
Blok 5 OK Jl. Rajawali Selatan Raya Kavling
C-5 No. 2 Kel. Pademangan Timur,
Kec. Pademangan, Jakarta Utara, DKI Jakarta - 14410
Telp : 021 - 6412557

GOB

Die Casting Series
Glue-On-Board Cabinet Indoor

1.86

PROJECT IMPLEMENTATION



AUDITORIUM



MULTIFUNCTION ROOM



RETAIL



WORSHIP

TANILED GOB uses Glue on Board (GOB) technology to provide maximum protection for the LED surface. It offers higher resistance to impact, dust, and high humidity, ensuring stable and reliable performance for long-term use in various environmental conditions.

PRODUCT SPECIFICATION

Parameter	Value
LED Type	GOB
Pixel pitch(mm)	1.86
Pixel density(Dots/m²)	288.906
Module dimension(mm)	320 x 160
Module resolution(pixels)	172 x 86
Module weight(kg)	0,413±0,02
Cabinet dimension(mm)	640x480mm
Material	Die-cast Aluminum Cabinet
Cabinet weight(kg)	≥6
Brightness(cd/m²)	450~500
Color temperature(K)	500~25000K Adjustable
Refresh Rate	7680Hz
Power Consumption (Max./Avg./module)(W)	300w/m² 90w/m²
IP Rating	Front IP65, rear IP30
Viewing Angle (H/V)	160/140
Typical value of chip life(H)	100.000
Operating Humidity Range (RH)	10%~95%

Catatan:
Disarankan menyiapkan spare daya sekitar 30% agar LED Display bekerja lebih stabil dan menghadirkan performa terbaik setiap saat