



CONTACT US

Komplek Perkantoran Multiguna Kemayoran
Blok 5 OK Jl. Rajawali Selatan Raya Kavling
C-5 No.2 Kel. Pademangan Timur, Kec.
Pademangan Jakarta Utara, DKI Jakarta –14410
Telp : 021-6412557

IRIS 1.5

LED MODULAR INDOOR

Experience a New Spectrum of Color and Detail



FRONT
MAINTENANCE



3D EFFECT



HIGH REFRESH
RATE



CUSTOMIZED
SIZE

PROJECT IMPLEMENTATION



TV STUDIO



COMMAND CENTER



MUSEUM



MEETING ROOM

With TANILED IRIS, businesses can present ads, branding message, and engaging content in a dynamic and impactful way

PRODUCT SPECIFICATION

CATEGORY	IRIS 1.5
Pixel Pitch (mm)	1.53
LED Type	SMD
Modul Size (W*H,mm)	320x160
Modul Resolution (W*H,pixel)	208x104
Modul Weight (gram)	510
Pixel Density (Pixel/m²)	432,640
Brightness (cd/m²)	≥700cd
Power Consumption (Max. AVG.) (W/m²)	700W/m²/350W/m²
Refresh Rate (Hz)	≥7680Hz
Grayscale (Bit)	14-bit Color Processing Depth
Viewing Angel (H/V)°	120/140
Input Signal	HDMI, DVI/VGA.RGBH Composite, S-Video, YPbPr(HDTV) etc.
IP Rate	IP30
Recommend View Distance (m)	≥1,6m~25m
Operating Humidity Range (RH)	10%~95%
Operating Temperature Range (°C)	-10°~+65°
Maintenance	Front
Lifespan(Hours)	100.000

Catatan :
Disarankan menyiapkan spare daya sekitar 30% agar LED Display bekerja lebih stabil dan menghadirkan performa terbaik setiap saat